

Disque diamanté - CS 40


GÖLZ®

CS 40 - Béton Technique

 Coupe à eau

Caractéristiques :


- Soudé laser pour scies à sol faible puissance (jusqu'à 13 Cv)
- Hauteur segments 10 mm



Conforme  et EN13236

Applications :

- Béton, béton armé



Données techniques

Ø (mm)	Alésage (mm)	Segments (mm)				Code article
		L	I	H	Nb.	
300	25,4	40	2,8	10	20	CS40 301
350	25,4	40	2,8	10	24	CS40 351
400	25,4	40	3,2	10	28	CS40 401
450	25,4	40	3,6	10	32	CS40 451
500	25,4	40	3,6	10	36	CS40 501
600	25,4	40	4	10	40	CS40 601

Vitesse d'utilisation conseillée selon les matériaux

Matériaux	granit		marbre reconstitués carrelage	béton		asphalte
	riche en quartz	pauvre en quartz		non-armé	armé	
Vitesse périphérique en m/sec	25 - 30	32 - 40	40 - 50	30 - 50	30 - 40	45 - 60

Lire les informations de sécurité 

Portez des lunettes de protection 

Portez un casque de chantier 

Portez un casque de protection 

Portez un masque de protection 

Portez des chaussures de sécurité 

Portez des gants de protection 